



SPECIFICATION

Okitsumo Fluororesin Paint

NA801 TYPE

Heat resistance : 250	Drying : Baking	Construction : 1 coat	Color: Toning (*1)	Gloss: Semi gloss
---------------------------------	---------------------------	---------------------------------	------------------------------	-----------------------------

(* 1) There are limit to tone the color, please contact us.

CARACTERISTIC

This is balanced paint for non-stick, adhesion and corrosion resistance by 1 coat.
Excel in adhesion for stainless. (no need to blast treatment).

MATERIAL

Aluminum, Stainless, Galvanized steel plate, Aluminizing steel plate.

APPLICATION

Hair iron, Hair curler, Fan heater, Iron base.

COATING METHOD

PREPARATION	Degreasing	
COTAING METHOD	Brush or spray (*2)	
DILUTION	Brush	4476 thinner
	Spray	6805 thinner
DILUENT	Brush	0 - 10wt%
	Spray	10 - 30wt%
FILM THICKNESS (Dry)	10 - 20 μ m	
COATING TIMES	1 time	
STANDARD BUDGET	200g/m ² /time	
PRE-DRYING	80 - 100 X 100mins	
DRYING	380 x 15mins (*3)	

(*2) Before use, mix well and disperse again.

(*3) When baking it, it generates gasification fluorine compound so that exhaust and ventilate well.

* For repair, remove the film coat by blasting and recoat then recoat it and baking draying.

PACKING 1Kg, 4Kg, 16Kg