



SPECIFICATION

1/2-B6

S1-NTB3203B-001

Okitsumo Lubricative Coating NTB-3203 (Black)

Heat resistance	200
------------------------	------------

Gloss	Semi gloss
--------------	-------------------

Composition	1coat
--------------------	--------------

Color	Black
--------------	--------------

Packaging	1component
------------------	-------------------

Material	<u>Aluminum , SPCC , Stainless</u>
-----------------	------------------------------------

Coating Specification

Preparation		Degreasing or blasting
Coating Method		Air splay , Electrostatic coating
Thinner	Splay	NTB3200 thinner
	Electrostatic coating	NTB3200 thinner
Dilution rate	Splay	0 ~ 30 wt%
	Electrostatic coating	10 ~ 30wt%
Number of coatings		1 coating
Preliminary drying		80 ~ 100 / 5 ~ 15min
Drying		180 ~ 200 / 20 ~ 30min
Film thickness		10 ~ 30 μm

NOTANDUM FOR COATING

[ENVIRONMENTAL]

- Do not use the paint under the non porous area.

[PREPERATION]

- Remove the oil, moisture and stains on the surface of material by degreasing or blast.
- The adhesion will be superior by blast treatment.
- Blasted material is easy to rust so that please paint it at once.

[ADJUSTMENT]

- Mix it well before use. Because the pigment contained in a heat resistance paint is easy to settle. The poor mixing will make peeling or bad gloss.
- Use specified thinner.
- Do not mix other paints. Mixing foreign material such as water or oil will make bad film.
- Use it after filter by 100 – 160 stainless-steel mesh.

[COATING]

- The paint in tank, please coat with it while stirring by automatic mixture.
- Please keep the film thickness within the standard value. If it will be over the value, it will blister after heat it.
- Don't coat it on the heating material.

[DRYING]

- When you heat-dry the coating film, the organic gas is generated so that please ventilate inside of the furnace
- Please dry it in specified condition. If the dry is incomplete, it may cause inferior goods such as insufficient hardness.

[OTHERS]

- The coating film may cause softening by heat, please care if you put a hot thing on it.

[DISPOSITION]

- Please request a specialized company to dispose the unused paint or waste fluid and subject to the law of county and local governing.

[HANDLE WITH CARE]

- Includes flammable organic solvent so that do not use near fire.
- Irritate to the skin, mucous and specially eyes, care not to touch the paint. If touch it, clean with a large quantity of water.
- For details, please refer to the MSDS.